

Economic Glossmeter



This lightweight and compact glossmeter uses a built-in standard board and is used for measuring the gloss of paint; film; ink; plastics etc.

Key Features

Relevant Standards: ISO 2813; ASTM D 523; ASTM D 2457

Cost-effective- easy to use compact precise and reliable

3. 5-inch colour screen; high resolution (480×320)

Shows 5 groups of testing results simultaneously

T01-21011 enables simultaneous testing at three angles (20°/60°/85°)

Data storage function - max. 1000 groups

Calibrates automatically when turned on

Built-in lithium ion rechargeable battery

USB/RS 232 interface for printer connection

Auto power-off

Product Code	T01-21010	T01-21011 (20°/60°/85°)
Measuring Range	0~300 GU	20°/60°: 0~1000 GU 85°: 0~160GU
Measuring Aperture	9×15 mm	20°:10×10 60°:9×15 85°:5×36 mm
Resolution	GU:0.1	GU:0.1
Dimensions	160×75×90 mm	160×75×90 mm
Weight	350 g	350g

Ascott Analytical Equipment Limited

6-8 Gerard, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UW, Great Britain

T +44 (0) 1827 318040 F +44 (0) 1827 318049 E sales@ascott-analytical.com W www.ascottshop.com