

## Portable Conductivity Meter



Portable Conductivity Meter with automatic calibration, automatic temperature compensation, data storage, function set-up, automatic power-off and low voltage display. It can also switch between conductivity, Total Dissolved Solids (TDS), salinity and resistivity. Multinomial calculation for TDS and salinity

Includes:

Conductivity Meter

Plastic conductivity electrode

50ml 1,413  $\mu\text{S}/\text{cm}$  conductivity standard solution

Replacement AA Batteries

Ascott Analytical Equipment Limited

6-8 Gerard, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UW, Great Britain

T +44 (0) 1827 318040 F +44 (0) 1827 318049 E sales@ascott-analytical.com W www.ascottshop.com

## Key Features

Measuring range:  $0 \sim 2 \times 10^5 \mu S / cm$

Resolution: 0.01/0.1/1 $\mu$ S/cm:0.01/0.1 mS/cm

Accuracy: Meter:  $\pm 1.0\%$  FS Overall:  $\pm 1.5\%$  FS

Temp. compensation range: (0 ~ 50) °C (Automatic)

Data storage: 200 groups (Series number; measuring value measuring unit and temperature)

Power: Two AA batteries (1.5V x2)

Dimensions: 250×210×50mm (L×W×H)

Weight: 1.6kg

Product Code: T01-60853

## Accessories

Plastic Conductivity Electrode-Product Code: T01-60854

Glass Conductivity Electrode-Product Code: T01-60856