

Automatic Film Applicator



Automatic film applicators allow for precise coating and eliminate errors caused by inconsistencies in manual applications.

Key Features

Adjustable variable speed: 2~100mm/s

Specifically designed bracket and flexible system for all substrates

Variable starting point for different size substrates

Can be used with the range of applicators and wire bars supplied by Ascott

External vacuum pump – avoiding the vibration disturbance of an internal pump Model

T01-700157 has an additional heating function

Product Code	T01-700155	T01-700156	T01-700157*
Drawdown Bed Size	360 × 250 mm	490 x 250 mm	360 x 250 mm
Vacuum Bed Area	290 x 190 mm	410 x 190 mm	290 x 190 mm
Max. Application Length	250 mm	375 mm	250 mm
Drawdown Speed	2-100 mm/s	2-100 mm/s	2-100 mm/s
Carriage Holder Weight	1kg	1kg	1kg
Dimensions	500×345×340mm	635×345×340mm	500×345×340mm
Weight	40 kg	46 kg	42 kg

*Temperature Range: RT+5°C~100°C, Temperature Uniformity:±5°C

Ascott Analytical Equipment Limited

6-8 Gerard, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UW, Great Britain

T +44 (0) 1827 318040 F +44 (0) 1827 318049 E sales@ascott-analytical.com W www.ascottshop.com