

## Precise Digital Overhead Stirrer



High quality precise digital overhead stirrers with brushless motor for smooth and reliable operation. Auto cut off for safety and capable of running for extended periods of time

Ascott Analytical Equipment Limited

6-8 Gerard, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UW, Great Britain

T +44 (0) 1827 318040 F +44 (0) 1827 318049 E [info@ascottshop.com](mailto:info@ascottshop.com) W [www.ascottshop.com](http://www.ascottshop.com)

### Key Features

- CE TUV us and FCC certified
- Auto shut-off for overheating or overload
- Smooth start up to avoid sample spills and splashes
- Closed case prevents ingress in accordance with DIN/EN60529,
- Dimensions (W×H×D) 83x220x186 mm

| Ordering Information →<br>Parameters ↓ | T01-701000            | T01-701001 | T01-701002   | T01-701003 | T01-711004    |
|--|-----------------------|------------|--------------|------------|---------------|
| Max. Stirring Capacity                 | 20 L                  |            | 40 L         |            | 70 L          |
| Motor Rating Input, W                  | 60 W                  |            | 120 W        |            | 180 W         |
| Motor Rating Output, W                 | 50 W                  |            | 100 W        |            | 160 W         |
| Power                                  | 70 W                  |            | 130 W        |            | 200 W         |
| Timing Function                        | ---                   |            |              |            | 0~99h 59min   |
| Speed Range, rpm                       | 50-2,200 rpm          |            |              |            | 50-1,100 rpm  |
| Speed Display Accuracy, rpm            | ± 3 rpm               |            |              |            | ± 10 rpm      |
| Display                                | LED                   | LCD        | LED          | LCD        | LCD           |
| Voltage/Frequency                      | 100V~240V ; 50HZ/60HZ |            |              |            |               |
| Max. Torque                            | 40 N.cm               |            | 60 N.cm      |            | 300 N.cm      |
| Max. Viscosity                         | 10,000 mPa.s          |            | 50,000 mPa.s |            | 100,000 mPa.s |
| Chuck Range Diameter                   | 0.5mm-10mm            |            |              |            |               |
| Dimensions (W×H×D)                     | 83x220x186 mm         |            |              |            |               |
| Weight                                 | 2.4 KG                |            | 2.8 KG       |            | 3.2 KG        |



Ascott Analytical Equipment Limited

6-8 Gerard, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UW, Great Britain

T +44 (0) 1827 318040 F +44 (0) 1827 318049 E info@ascottshop.com W www.ascottshop.com