

DuPont Impact Tester



The DuPont Impact Tester has been designed to test the endurance of coated material, when impacted by a falling weight at specified points. The purpose of the test is to see if test specimens can resist the effect of rapid impact testing. The principle of the test is that a coated test specimen is impacted by a falling weight, at a fixed height; thus checking the damage or deformation of the test specimen.

The DuPont Impact Tester can also be used on paintings with coated materials. The same procedure is followed, using various impact heads or needles to drop freely onto the test specimen from a certain height. This is performed three times on the same test specimen, which is then left to stand for one hour. The test specimen is then checked for any cracking on the painting.

Key Features

Product Code: T01-710160

Relevant Standards: ASTM D 2794 JISK 5400 CNS 10756

Instrument scale Length: 50-500mm (grade: 50mm)

Mass of hammer: 300g 500g 1000g

Piercer specification: 1/2 1/4 1/8 1/16 3/16 in

Notch diameter on the bolster block: 1/2 1/4 1/8 1/16 3/16in

Ascott Analytical Equipment Limited

6-8 Gerard, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UW, Great Britain

T +44 (0) 1827 318040 F +44 (0) 1827 318049 E sales@ascott-analytical.com W www.ascottshop.com